



NOTES:

- MATERIAL:
  - MOLDING: LCP UL94 V-0
  - CONTACT: COPPER ALLOY.
  - G/F ON CONTACT AREA, 100u''
  - Min TIN (LEAD FREE) ON SOLDER AREA,
  - SHELL: SUS304-H, T=0.30±0.03mm
  - 50u'' NICKEL PLATING OVER ALL.
  - SHILD: SUS304-H, T=0.12±0.03mm
- MECHANICAL:
  - INSERTION: 5°~20N.
  - EXTRACTION: 8°~20N.
  - DURABILITY: 10000 CYCLES
- ELECTRICAL:
  - CURRENT: 5A MIN FOR VBUS;
  - 0.25A MIN FOR OTHER.
  - VOLTAGE: 20 V MAX
  - WITHSTANDING VOLTAGE: 100V AC.
  - CONTACT RESISTANCE: 40mΩ MAX.
  - INSULATION RESISTANCE: 100MΩ MIN.
- ENVIRONMENTAL
  - TEMPERATURE RANGE -55° C ~ +85° C

料号编码:

XXX - XX XX XX X X XXXX

公司名称						产品识别流水码
产品类别						
A-USB A F-母座						
B-USB B M-公头						
C-USB C						
M-MICRO						
N-MINI						
产品上板形态						
L-立式						
M-卧式						
S-贴片						
D-插件						
C-沉板						
J-夹板						
H-焊线						
XF-防水系列产品						
X=上板类型						
PIN 数						
06:6PIN						
16:16PIN						
24:24PIN						
以此产品为准						
包装方式						
1. TRAY (吸塑盒)						
2. TAPE (编带)						
3. TAPE (袋装)						

**ZDX** 深圳市兆达鑫科技有限公司  
Shenzhen zhaodaxin Technology Co., Ltd

TITLE:		PART NO.: ZDX-CFMDS242WL03		
TYPE-C/F 24PIN 板上L=10.0 无固定脚 DIP+SMT		TEL: 0755-29888153		
工程图		WEB: <a href="http://www.szzdjmkj.com/">http://www.szzdjmkj.com/</a>		
THIRD ANGLE PROJECTION	UNIT:	SCALE:	SIZE:	SHEET:
	mm	1:1	A4	1/2